

APPENDIX A

```

5  IF (it is time to perform housekeeping activities) THEN
    FOR (each TCP connection that has started to close, i.e. observed the TCP FIN flag set) DO
      IF (the time allowed for closure has passed) THEN
        Close this connection
      IF (this is the last connection with this user) THEN
        Reinitialize the user's profile and set the profile state to Incomplete
      ENDIF
    ENDIF
  NEXT

15  FOR (each connection that has been idle for the maximum allowed time) DO
    Close this connection
  IF (this is the last connection with this user) THEN
    Reinitialize the user's profile and set the profile state to Incomplete
  ENDIF
20  NEXT
ENDIF

25  IF (it is an IP packet) THEN
    IF (it is an IP/UDP packet) THEN
      Check the source and destination ports against a list of allowed well-known UDP ports
    IF (either port is on the allowed port list) THEN
      IF (the server port is for the XDMCP protocol) THEN
        Check the XDMCP Opcode against a list of allowed opcodes
      IF (the XDMCP Opcode is on the allowed opcode list) THEN
```

SUBSTITUTE PATENT APPLICATION

Check if the XDMCP packet is being sent in an allowed direction

```

35 IF (an allowed Opcode is being sent to the server or an allowed Opcode is being sent to the user) THEN
    IF (there is an established X-Windows connection with this user) THEN
        IF (the Opcode is other than KeepAlive or Alive) THEN
            Discard the packet
            ENDIF
        ELSE
            IF (the Opcode is KeepAlive or Alive) THEN
                Discard the packet
                ENDIF
            ENDIF
        ENDIF
    Create and initialize a profile for this user
    Set the profile state to Incomplete
    IF (the Opcode is Query) THEN
        Reinitialize the user's profile and set the profile state to Incomplete
    FOR (each Authentication Name in the packet) DO
        IF (the Authentication Name is not recognized) THEN
            Discard the packet
            ENDIF
        NEXT
        Remember the Authentication Names in the user's profile
    ELSE IF (the Opcode is Willing) THEN

```

SUBSTITUTE PATENT APPLICATION

IF (the Authentication Name in the packet is not recognized) THEN
 Discard the packet
ENDIF

65

IF (the Authentication Name is not one of the authentication names recorded in the user's
 profile from the Query packet) THEN
 Discard the packet
ENDIF

70

Remember this Authentication Name in the user's profile

IF (the Hostname supplied by the server is NOT syntactically valid) THEN
 Discard the packet
ENDIF

75

IF (the Status string is NOT composed of printable characters) THEN
 Discard the packet
ENDIF

80

ELSE IF (the Opcode is Unwilling) THEN
 IF (the Hostname supplied by the server is NOT syntactically valid) THEN
 Discard the packet
 ENDIF

85

IF (the Status string is NOT composed of printable characters) THEN
 Discard the packet
ENDIF

Reinitialize the user's profile and set the profile state to Incomplete

90

SUBSTITUTE PATENT APPLICATION

ELSE IF (the Opcode is Request) THEN
 IF (the X Display Number is invalid) THEN
 Discard the packet
 ENDIF
 ENDIF

95

Remember this Display Number in the user's profile

FOR (each Connection Type in the packet) DO
 IF (the Connection Type is not IP) THEN
 Discard the packet
 ENDIF
 NEXT

100

FOR (each Connection Address in the packet) DO
 IF (the Connection Address is not an IP address) THEN
 Discard the packet
 ENDIF

105

IF (the Connection Address does not match the user's IP address) THEN
 Replace the Connection Address with the user's IP address
 ENDIF
 NEXT

110

IF (none of the Connection Addresses matched the user's IP address) THEN
 Discard the packet
 ENDIF

115

IF (the Authentication Name in the packet is not recognized) THEN

SUBSTITUTE PATENT APPLICATION

```

120         Discard the packet
        ENDIF

125     IF (the Authentication Name does not match the Authentication Name recorded in the user's
        profile from the Willing packet) THEN
            Discard the packet
        ENDIF

130     IF (the lengths of the Authentication Name and Authentication Data are not both zero or
        non-zero) THEN
            Discard the packet
        ENDIF

135     FOR (each Authorization Name in the packet) DO
        IF (the Authorization Name is not recognized) THEN
            Discard the packet
        ENDIF
        NEXT

140     Remember the Authorization Names in the user's profile

    IF (if the Manufacturer Display ID contains invalid characters) THEN
        Discard the packet
    ENDIF

145     IF (if the Manufacturer Display ID does not match any previous recorded Display ID for this
        user) THEN
        Discard the packet
    ENDIF

```

SUBSTITUTE PATENT APPLICATION

150 ELSE IF (the opcode is Accept) THEN
Remember the Session ID in the user's profile

155 IF (the Authentication Name in the packet is not recognized) THEN
Discard the packet
ENDIF

160 IF (the Authentication Name does not match the Authentication Name recorded in the user's
profile from the Request packet) THEN
Discard the packet
ENDIF

165 IF (the lengths of the Authentication Name and Authentication Data are not both zero or
non-zero) THEN
Discard the packet
ENDIF

170 IF (the Authorization Name in the packet is not recognized) THEN
Discard the packet
ENDIF

175 IF (the Authorization Name does not match any of the Authorization Names recorded in the
user's profile from the Request packet) THEN
Discard the packet
ENDIF

Remember the Authorization Name in the user's profile

SUBSTITUTE PATENT APPLICATION

180 IF (the lengths of the Authorization Name and Authorization Data are not both zero or non-
zero) THEN
 Discard the packet
ENDIF

185 ELSE IF (the opcode is Decline) THEN
 IF (the Status string is NOT composed of printable characters) THEN
 Discard the packet
 ENDIF

190 IF (the Authentication Name in the packet is not recognized) THEN
 Discard the packet
ENDIF

195 IF (the Authentication Name does not match the Authentication Name recorded in the user's
profile from the Request packet) THEN
 Discard the packet
ENDIF

200 IF (the lengths of the Authentication Name and Authentication Data are not both zero or
non-zero) THEN
 Discard the packet
ENDIF

Reinitialize the user's profile and set the profile state to Incomplete

205 ELSE IF (the opcode is Manage) THEN
 IF (the Session ID does not match the Session ID recorded in the user's profile from the
Accept packet) THEN

SUBSTITUTE PATENT APPLICATION

Discard the packet
ENDIF

210 IF (the X Display Number is invalid) THEN
Discard the packet
ENDIF

215 IF (the Display Number does not match the Display Number recorded in the user's profile
from the Request packet) THEN
Discard the packet
ENDIF

220 IF (if the Display Class contains invalid characters) THEN
Discard the packet
ENDIF

225 IF (if the Display Class does not match any previous recorded Display Class for this user)
THEN
Discard the packet
ENDIF

Set the user's profile state to Complete

230 ELSE IF (the opcode is Refuse) THEN
IF (the Session ID does not match the Session ID recorded in the user's profile from the
Accept packet) THEN
Discard the packet
ENDIF

235

SUBSTITUTE PATENT APPLICATION

```
ELSE IF (the opcode is Failed) THEN
  IF (the Session ID does not match the Session ID recorded in the user's profile from the
  Accept packet) THEN
    Discard the packet
  ENDIF
240

IF (the Status string is NOT composed of printable characters) THEN
  Discard the packet
  ENDIF

  Reinitialize the user's profile and set the profile state to Incomplete
245

ELSE IF (the opcode is KeepAlive) THEN
  IF (the X Display Number is invalid) THEN
    Discard the packet
  ENDIF
250

IF (the Display Number does not match the Display Number recorded in the user's profile
from the Manage packet) THEN
  Discard the packet
  ENDIF
255

IF (the Session ID does not match the Session ID recorded in the user's profile from the
Manage packet) THEN
  Discard the packet
  ENDIF
260

ELSE IF (the opcode is Alive) THEN
  IF (the Session Running flag is not 0 or 1) THEN
```

SUBSTITUTE PATENT APPLICATION

```
265         Discard the packet
        ENDIF

270     IF (the Session Running flag is True) THEN
        IF (the Session ID does not match the Session ID recorded in the user's profile from
        the Manage packet) THEN
            Discard the packet
        ENDIF
        ELSE – the Session Running flag is False
        IF (the Session ID is not zero) THEN
            Discard the packet
        ENDIF

275     Reinitialize the user's profile and set the profile state to Incomplete
        ENDIF

280     ELSE – the XDMCP Opcode is not allowed
        Discard the packet
        ENDIF

285     ELSE – the XDMCP Opcode is being sent in the wrong direction
        Discard the packet
        ENDIF
        ELSE – the XDMCP Opcode is not on the allowed-opcodes list
        Discard the packet
        ENDIF

290     ELSE – the server port is not for the XDMCP protocol
        Discard the packet
        ENDIF
        ELSE – neither of the IP ports are on the allowed-ports list
```

SUBSTITUTE PATENT APPLICATION

295 Discard the packet
 ENDIF

 ELSE IF (it is an IP/TCP packet) THEN
 IF (this packet is for an established TCP connection) THEN
 IF (the TCP RST flag is set) THEN
300 Close this connection immediately

 IF (this is the last connection with this user) THEN
 Reinitialize the user's profile and set the profile state to Incomplete
 ENDIF

305 ELSE IF (the TCP FIN flag is set for the first time for this connection) THEN
 Remember that the FIN flag was set in the user's profile

 Record that the FIN flag was observed at the current date/time
 ENDIF

310 ELSE -- the packet is not for an established TCP connection
 IF (the packet TCP SYN flag is set and the TCP ACK flag is not set) THEN
 Check the source and destination ports against a list of allowed well-known TCP ports

315 IF (either port is on the allowed port list) THEN
 Check if the TCP connection is being opened in an allowed direction, i.e. the SYN packet is from the
 server to an allowed user port or from the user to an allowed server port

320 IF (the TCP connection is being opened in an allowed direction) THEN
 Check if the user port is for the X-Windows protocol

 IF (this is an X-Windows connection) THEN

SUBSTITUTE PATENT APPLICATION

```
325 IF (there is not an existing profile for this user) THEN
      Discard the packet
    ELSE – there is an existing profile for this user
      IF (the state of the user's profile is not Complete) THEN
        Discard the packet
      ENDIF
330 IF (the user port does not correspond to the X Display Number in the user's profile)
    THEN
      Discard the packet
    ENDIF
335 ENDIF
      Remember this connection in the user's profile
    ELSE – the TCP connection is being opened in a disallowed direction
      Discard the packet
340 ENDIF
    ELSE – neither of the IP ports are on the allowed-ports list
      Discard the packet
    ENDIF
    ELSE – this is not a TCP SYN packet
      Discard the packet
345 ENDIF
      Remember the current date/time as that of the last packet on this connection
    ELSE – it is neither and IP/UDP or IP/TCP packet
      Discard the packet
350
```

SUBSTITUTE PATENT APPLICATION

355 ENDIF
 ELSE – it is a non-IP packet
 Discard the packet
 ENDIF